



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/093917 A1

- (51) **International Patent Classification⁷:** **H01S 5/14,**
5/0687

(21) **International Application Number:**
PCT/GB2005/001172

(22) **International Filing Date:** 21 March 2005 (21.03.2005)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
0406541.3 24 March 2004 (24.03.2004) GB

(71) **Applicant (for all designated States except US):** **UNIVERSITY OF STRATHCLYDE** [GB/GB]; 16 Richmond Street, Glasgow G1 1XQ (GB).

(72) **Inventors; and**

(75) **Inventors/Applicants (for US only):** **ABRAM, Richard, H.** [GB/GB]; 1/3 Drumsheugh Gardens, Edinburgh EH3 7QJ (GB). **GARDNER, Kyle, S.** [GB/GB]; 10 Kirdkene Plane, Newton Mearns, Glasgow, G77 5SB (GB). **RIIS, Erling** [DK/GB]; 8 Campsie Dene Road, Blanefield G63 9BN (GB).


(74) **Agent:** **KENNEDYS PATENT AGENCY LIMITED;** Floor 5 Queens House, 29 St Vincent Place, Glasgow G1 2DT (US).

(81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

- (54) Title:** IMPROVED MODE SELECTION AND FREQUENCY TUNING OF A LASER CAVITY



- (57) Abstract:** A technique for stabilising and scanning a cw-laser cavity (3) is demonstrated. The technique involves the incorporation of an intracavity birefringent etalon (15). Such an etalon provides a means for deriving a polarised electric field component (17) from an intracavity electric field (16) of the laser cavity, the orientation of polarisation of the polarised electric field component being dependent on the frequency and polarisation of the intracavity electric field (16). Appropriate analysis of this polarised electric field component (17) enables the laser cavity to be stabilised and frequency tuned while ensuring single mode operation.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.